

Type1 AS Smart AC Charging Point 48A/40A



- Fast charging, 48A,40A
- Easy installation& maintenance
- Solar charging and DLB (dynamic load balance management)
- Simple&classic design mobile APP control RFID,plug&play
- Full chain encryption
- High reliability long-term use of 50,000 times with relely
- FCC certification
- Multiple security protections
- Ground Fault Circuit Interrupter,Integrated, CCID20
- WiFi/Bluetooth/4G Ethernet communications
- IP55,IK10
- OCPP,OTA Smart scheduled charging

SPECIFICATION

Item	Description	
AC Power Supply	L1 + L2 + PE, single phase	
Rated Power	EAW-AS11W101-20 EAW-AS11W101- 10	11.52kW
	EAW-AS09P101-20 EAW-AS09P101- 10	9.6kW
Rated Voltage	AC 200-240V	
Rated Current	EAW-AS11W101-20 EAW-AS11W101- 10	6-48A
	EAW-AS09P101-20 EAW-AS09P101- 10	6-40A
Rated Current	EAW-AS11W101-20 EAW-AS11W101- 10	Hardwired
	EAW-AS09P101-20 EAW-AS09P101- 10	Hardwired NEMA 6-50 plug NEMA14-50 plug
Frequency	60Hz	
Connector Type	Type 1	
Cable Length (plug included)	25 feet (7.62 m)	
Charging Control	mobile app RFID Plug-and-charge	
Display Screen	EAW-AS11W101-20 EAW-AS09P101-20	3.8-inch LCD screen
Indicator Lights	EAW-AS11W101- 10 EAW-AS09P101- 10	4 LEDs
Connectivity	Basis: Wi-Fi (2414MHz-2484MHz 802. 11b/g/n) Bluetooth (2402MHz-2480MHz BLE5.0) Optional: 4G, LAN	
Communication Protocol	OCPP 1.6-J	
Protection	Over current protection, over voltage protection, under voltage protection, over temperature protection, leakage protection, unconnected PE ground protection, lightning protection	
Ground Fault Circuit Interrupter	Integrated, no additional required (CCID20)	
Operating Altitude	2000m	
Storage Temperature	-40°F - 185°F (-40°C - 85°C)	
Operating Temperature	- 12°F - 122°F (-25°C - 50°C)	
Relative Humidity	95%RH, No water droplet condensation	
Vibration	0.5G, No acute vibration and impaction	
Installation Location	Indoor or outdoor, good ventilation, no lammable, explosive gases	
Weight	13.2 lbs. (6KG)	
Dimension (H x W x D)	13 x 8 x 4 in (388 x 202 x 109 mm)	
Mounting	Wall-mounted or pole-mounted (mounting pole is optional)	
IP Code	IP66 (wallbox), IP54 (connector)	